



141 Unheated 142 High Temperature

BARATRON® VACUUM PRESSURE SWITCHES

The 141 and 142 Vacuum/Pressure Switches offer fast, accurate, and reliable protection for vacuum equipment and processes. Designed for applications where a DC signal output is not required, the 141 and 142 provide relay outputs that are readily interfaced with alarms, valve actuators, computers, process controllers, or other protection devices.

Based on the well-known MKS Baratron® capacitance manometer principle of operation, the 141/142 sense the deflection of a diaphragm due to applied pressure, providing a switched output when pressure exceeds the chosen set point. An LED provides visual "above set point" indication, and facilitates adjustment of the set point. The dual electrode sensor is an all-metal, all-welded design, thus exposing only corrosion-resistant Inconel to the process gases.

The 142 is a heated (100°C) version of the 141, and is designed to help minimize process effluent buildup that can occur in LPCVD nitride, aluminum etch, and other types of processes.

Features & Benefits

- Ideal for protection of expensive equipment or processes: high vacuum pumps, mass spectrometers, lasers, plasma systems
- Fully adjustable set point: from 0.2% to 100% of Full Scale
- High accuracy set point: 0.5% of Full Scale
- Corrosion resistant: all-metal, all-welded construction exposes only Inconel® and stainless steel to gases
- Double pole, two Form C relay contacts
- Fast response switching: 20 msec
- Provide inexpensive process control for opening/closing slow pump and isolation valves, and for turning on/off various types of pumps

Pressure &

Vacuum Measurement
Solutions

WWW.MKSINST.COM



Specifications and Ordering Information

Full Scale Ranges

Set Point Range

Accuracy

Temperature Coefficients

Zero

Span

Ambient Operating Temperature

Response Time

Material Exposed to Process

Internal Volume³

Overpressure⁴

Outputs

Electromechanical relay

Input Power Required

Fittings⁵

Standard

Optional

1, 2, 10, 100, 1000 Torr (mmHg) absolute¹

(Other engineering units available on special order, consult Applications Engineering.)

0.2% to 100% of F.S.²

±0.5% of range (± temperature coefficients)

141: ±0.04% of F.S./°C

142: ±0.015% of F.S./°C

141: ±0.06% of set point/°C

142: ±0.03% of set point/°C

141: 0° to 50°C

142: 20° to 70°C; sensor is temperature controlled at 100°C

< 20 msec from 0 to F.S.

Inconel and 316 S.S.

7.0 cc

120% of F.S. or 35 psia (1000 mmHg), whichever is larger

DPDT (isolated) contacts rated at 2 amps @ 30VDC or 1 amp @ 120VAC resistive. Relay is energized when pressure is above set point. Fail-safe operation provides for the relay to be energized when pressure is below set point. For compliance, voltages cannot equal or exceed either 50 VAC or 75 VDC.

141: +20 to +30 VDC, 72 mA max. (60 mA @ 24 VDC)

142: +20 to +30 VDC, 1.2 Amps max. (875 mA @ 24 VDC)

0.5" (12.7 mm) tubulation

Swagelok® 8 VCR® (female), mini-CF, NW 16 KF, Swagelok 8 VCO®

¹If gauge pressure set point actuation is desired on the 141, 142, add SP110-89 to end of ordering code.

²Unit shipped with set point at 50% of F.S. unless otherwise specified.


³5K-25K Torr units have an 8.5 cc volume.

⁴1 and 2 Torr F.S. units have a max. overpressure of 25 psia.

⁵Ranges above 1000 Torr are available with certain fittings; consult Applications Engineering.

Ordering Code Example: 141AA-00001AA

141 and 142	Code	Configuration
Numbers	141AA/142AA	141AA
Full Scale Ranges		
1 mmHg	00001	00001
2 mmHg	00002	
10 mmHg	00010	
100 mmHg	00100	
1000 mmHg	01000	
Fittings		
½" dia. tubulation	A	A
Swagelok 8 VCR (female)	B	
Mini-CF, rotatable	C	
NW 16 KF	D	
Swagelok 8 VCO (female)	E	
Relay Mode		
Standard operation (energizes above set point)	A	A
Fail-safe operation (energizes below set point)	B	



Dimensional Drawing —

Note: Unless otherwise specified, dimensions are nominal values in inches (mm referenced).



MKS Instruments, Inc. Global Headquarters

2 Tech Drive, Suite 201
Andover, MA 01810

Tel: 978.645.5500

Tel: 800.227.8766 (in U.S.A.)

Web: www.mksinst.com

MKS Instruments, Inc. Pressure & Vacuum Measurement Solutions

Six Shattuck Road
Andover, MA 01810

Tel: 978.975.2350

141_2 - 1/18

© 2009-2018 MKS Instruments, Inc.
All rights reserved.

MKS products provided subject to the US Export Regulations. Diversion or transfer contrary to US law is prohibited.

Specifications are subject to change without notice. mksinst™ is a trademark and Baratron® is a registered trademark of MKS Instruments, Inc., Andover, MA. Swagelok®, VCR®, and VCO® are registered trademarks of Swagelok Marketing Co., Solon, OH. Inconel® is a registered trademark of Inco Alloys International, Huntington, WV.